

# Sonnenschein Solar

## Technical data sheet

### Technical features:

- Nominal capacity 6.60-230 Ah  $C_{100}$  (20 °C)
- Long shelf life up to 17 months at 20 °C without recharge due to the very low self discharge rate
- Excellent cycling performance – 800 cycles at 60% Depth of Discharge  $C_{10}$  (at 20 °C)

### Standards & certifications:

- Designed in accordance with IEC 61427 and IEC 60896-21/22
- Manufactured in Europe in our ISO 9001 certified production plants
- Trouble-free transport of operational cells, no restrictions for rail, road, sea, and air transportation (IATA, DGR, clause A67)
- Approval: UL (Underwriters Laboratories, USA), DNV GL (Germanischer Lloyd)



Nominal capacity  
6.60-230 Ah  $C_{100}$



Block battery



Grid plate



Recyclable



Valve regulated  
lead-acid  
batteries



Proof against  
deep discharge



Maintenance free  
(no topping up)



800 cycles at  
60% DoD  $C_{10}$

### Technical characteristics and data

Type	Part number	Nom. voltage	Nominal capacity	Discharge current	Length	Width	Height	Height	Weight*	Terminal	Terminal position
		V	$C_{100}$ 1.80 Vpc 20 °C	$I_{100}$	(l)	(w)	(h1)	(h2)	approx. kg		
			Ah	A	max. mm	max. mm	max. mm	max. mm			
S12/6.6 S	NGS01206D6HS0SA	12	6.60	0.06	152	65.5	94.5	98.4	2.60	S-4.8	3
S12/17 G5	NGS0120017HS0BA	12	17.0	0.17	181	76.0	-	167	6.10	G-M5	1
S12/27 G5	NGS0120027HS0BA	12	27.0	0.27	167	176	-	126	9.60	G-M5	1
S12/32 G6	NGS0120032HS0BA	12	32.0	0.32	197	132	160	179	11.1	G-M6	2
S12/41 A	NGS0120041HS0CA	12	41.0	0.41	210	175	-	175	14.2	A-Terminal	1
S12/60 A	NGS0120060HS0CA	12	60.0	0.60	261	136	208	230	18.0	A-Terminal	1
S12/85 A	NGS0120085HS0CA	12	85.0	0.85	353	175	-	190	25.5	A-Terminal	1
S12/90 A	NGS0120090HS0CA	12	90.0	0.90	330	171	213	236	28.2	A-Terminal	2
S12/130 A	NGS0120130HS0CA	12	130	1.30	286	269	208	230	36.7	A-Terminal	4
S12/230 A	NGS0120230HS0CA	12	230	2.30	518	274	216	238	63.5	A-Terminall	3

\* Actual weight may differ by ±5%


# Sonnenschein Solar

## Technical data sheet

### Capacities $C_1 - C_{100}$ (20 °C) in Ah

Type	$C_1$	$C_5$	$C_{10}$	$C_{20}$	$C_{100}$
	1.70 Vpc	1.70 Vpc	1.70 Vpc	1.75 Vpc	1.80 Vpc
S12/6.6 S	2.90	4.60	5.10	5.70	6.60
S12/17 G5	9.30	12.6	14.3	15.0	17.0
S12/27 G5	15.0	22.1	23.5	24.0	27.0
S12/32 G6	16.9	24.4	27.0	28.0	32.0
S12/41 A	21.0	30.6	34.0	38.0	41.0
S12/60 A	30.0	42.5	47.5	50.0	60.0
S12/85 A	55.0	68.5	74.0	76.0	85.0
S12/90 A	50.5	72.0	78.0	84.0	90.0
S12/130 A	66.0	93.5	104	110	130
S12/230 A	120	170	190	200	230

### Drawings, terminal and torque



Not to scale!

